

35x PROFlex[®] X-Frame Ambulance Cot

Beracah
M E D I C A

Industry Leading Safety,
Stability & Performance



NEW

Distribuidor

ventas@beracahmedica.mx

Beracah
M E D I C A

662 15 10 979

35x PROFlex[®]

Ferno's 35X PROFlex[®] Ambulance Cot provides industry leading stability and safety when transferring and transporting patients.

STABLE X-FRAME DESIGN

A longer, fixed front leg in the X-Frame and carefully engineered X-frame geometry create a low center of gravity and provide minimal flex, creating industry leading stability. This means you may be less likely to flip or tip a cot during transfers and transport.



EZ PULL RELEASE SYSTEM

The NEW 35X EZ Pull™ release system reduces wrist strain and helps you position yourself before assuming the weight of the cot and patient. This helps you maintain proper body mechanics and prevents accidental movement of the legs before you're ready.



FEATURES

STABLE

- ▶ A Longer, Fixed Front Leg in the X-frame, and a rigid C-channel running the length of the cot, stiffens the cot and reduces side-to-side flexing.
- ▶ Lower center of gravity offers greater stability for patient transfers or while rolling.

MANEUVERABLE

- ▶ 5 Position Load Frame provides superior maneuverability and multiple lift positions for different size operators.
- ▶ 6" wheels (two with swivel-lock and rolling-lock) feature U-tread tires with increased surface area for better rolling and longer life
- ▶ Pull out side handles provide additional grip points for assistance with heavy patients
- ▶ 7 height positions, with true 360° turning radius in the lowest position

DURABLE

- ▶ All Metal Frame Construction means no plastic parts to wear out or fail
- ▶ Innovative L-Castings technology increases durability and reduces maintenance costs
- ▶ Increased scuff strips for loading and unloading
- ▶ Cast aluminum housing on load wheels prevents bending under heavy loads
- ▶ Powder coated frame available in five color options

COMFORTABLE

- ▶ Wider Bed Surface for comfort and support of any size patient.
- ▶ Wide head frame for large patients and extra elbow room during intubation & CPR
- ▶ Gas assist back rest and shock position for rapid patient positioning

SAFE

- ▶ No Pinch Points along the lifting mainframe
- ▶ Smooth, clear-coat-finish side rails keep hands clean, are impervious to blood and pathogens, and prevent unsightly wear and tear
- ▶ Heat sealed mattress is impervious to blood and pathogens
- ▶ Swing down side arms have no pinch points and can be used to tuck patient in
- ▶ Safety bar and hook provide safety while unloading from ambulance
- ▶ Conforms to the Federal Specification for the Star-of-Life Ambulance KKK-A-1822E

SPECIFICATIONS

Length:	Maximum:	79" (201 cm)
	Minimum:	64" (163 cm)
Width:		24 (61 cm)
Bed Height Range:		13.75"- 38.5" (35-98 cm)
Max Loading Height:		34" (86 cm)
Weight:		89 lb. (40.5 kg)
Load Limit:	Loading Position:	700 lb. (318 kg)
	Lowest Position:	1100 lb. (450 kg)